

ENGINE	
TYPE	6.4 HEMI 392
NUMBER OF CYLINDERS, LAYOUT	V8
DISPLACEMENT (CM ³)	6.417
MAX POWER	470 HP/354 Kw @6.000 rpm
MAX TORQUE	637 Nm @ 4.300 rpm
FUEL INJECTION	Sequential Multi-Port Electronic
BORE X STROKE (MM)	103.9 x 94.5
COMPRESSION RATIO	10.9:1
NUMBER OF VALVES	16
PERFORMANCE	
TRANSMISSION	8HP75 Automatic, 8-Speed Overdrive
ACCELERATION 0-100 KM/H (SECONDS)	4,5
FRONT BRAKES MILITEM	Disco 370mm Semi floating disc assembly with aluminium bell, 6-Piston Radial Calipers, Braided Tubing
REAR BRAKES MILITEM	Disco 370mm Semi floating disc assembly with aluminium bell, 4-Piston Radial Calipers, Braided Tubing
EXHAUST SYSTEM MILITEM	Dual-Mode with 4 Black Terminal
TRANSMISSION 4WD	
OPERATING MODELS	4WD High; 4WD Auto; 4WD Neutral; 4WD Low
AXLE RATIOS	3.73 , 4.56
FUEL CONSUMPTIONS	
EMISSIONS STANDARDS	EURO 6D
FUEL CONSUMPTION – URBAN CYCLE (L/100 KM)	18,5
FUEL CONSUMPTION – EXTRA-URBAN CYCLE (L/100 KM)	14,3

FUEL CONSUMPTION – COMBINED CYCLE (L/100 KM)	16,5
COMBINED CYCLE EMISSIONS CO2 (G/KM)	357
WEIGHT AND DIMENSIONS	
KERB WEIGHT (KG)	2.315
TOWING CAPACITY (KG)	1.587
HEIGHT (MM)	1.893
WIDTH (MM)	1.875
LENGTH (MM)	4.785
WHEELBASE (MM)	3.008
GROUND CLEARANCE (MM)	262
STANDARD TIRES	ALL-TERRAIN 35 x 12,5/R20
FUEL TANK (L)	81
OTHER SPECS	
APPROACH/DEPARTURE/BREAKOVER ANGLE	44.5°/37.5°/22.6°
FRONT AXLE	3rd GENERATION DANA 44
REAR AXLE	3rd GENERATION DANA 44
SUSPENSIONS (FRONT/REAR)	MILITEM Adjustable High-Pressure gas charged Aluminium monotube shocks absorbers & hydraulic rebound stop with carbon protection and gas separate tank
LUBRICANTS	BARDAHL



Determined based on the measured CO2 emissions in consideration of the vehicle mass.